

ELECTRONIC TIMERS Outdoor Readability 35m

HCX9.6



Years

(non contractual picture)

Composition

- 1 Digital Clock 1 Infrared remote control
- 1 Cable control console for the timer
- Operating and installation instructions

Description

Use:	Outdoor	
Programming:	Infra-red remote control	
Readability:	35m, angle >160°	
Dimensions:	700 x 180 x 90mm	
Weight:	6 kg	
Power supply:	230V / 50-60Hz	Power consumed: 12VA
Protection:	Unbreakable mat polycarbonate front face	
Mains cable (supplied):	5 m – Type: 230V, 3G, 0.75 mm²	

Display functions

Timer: 6 red LED digits (9 cm) for:

- Count-up timer: hundredths / seconds / minutes (MM:SS)
- Count-down timer: (MM:SS)
- Timer mode: count-up or count-down from a set-value
- "Workout" modes: to manage sequences of exercises / rest periods.

Other available functions:

Other available functions:



Day counter

2

on oc u

Scoring

Temperature

Day time & Date

- Programming of the brightness (4 luminosity levels available)
- Eco-Mode: low luminosity between 23:00 and 06:00

Remote control

1 IR remote control (180 x 50 x 23 mm), clear range at 10m, for:

- Programming of the day time
- Programming of the date
- Programming of the display duration
- Programming of the transition effects
- Possibility to display a permanent information

1 cable control console: (140 x 150 x 40mm) cable 5m

- Programming of the timer
- Start / Stop / Reset the timer to 0

Options

DCF or GPS Antenna: Sensor: Slave clock Integrated buzzer Tripod For accurate time synchronisation For automatic air temperature display